
Overview

The HP Ethernet 10Gb 2-port 530FLR-SFP+ adapter features the next generation, single chip 10GbE solution from Broadcom in a FlexibleLOM form factor designed for select HP ProLiant Gen8 rack servers.

The HP 530FLR dual-port design with a total aggregate throughput of 20Gb meets the needs for customers desiring high bandwidth.

The HP 530FLR supports enterprise class features such as VLAN tagging, adaptive interrupt coalescing, MSI-X, NIC teaming (bonding), Receive Side Scaling (RSS), jumbo frames, PXE boot and virtualization features such as VMware NetQueue and Microsoft VMQ.

Support for HP Sea of Sensors 3D Technology enhances server performance while reducing energy use and expense.



Models

HP Ethernet 10Gb 2-port 530FLR-SFP+ Adapter

647581-B21

Kit Contents

- HP Ethernet 10Gb 2-port 530FLR-SFP+ Adapter
- Quick install card
- Product warranty statement

Compatibility

Servers

ProLiant DL (rack-optimized):

- HP ProLiant DL160 Gen8
- HP ProLiant DL360p Gen8
- HP ProLiant DL380p Gen8
- HP ProLiant DL385p Gen8
- HP ProLiant DL560 Gen8

ProLiant SL (scalable line):

- HP ProLiant SL230s Gen8
- HP ProLiant SL250s Gen8
- HP ProLiant SL270s Gen8

NOTE: This is a list of supported servers. Some may be discontinued.



Standard Features

Product Features

- Flexible-LOM for select HP Rack servers
- Industry-leading throughput and latency performance
- Up to 40Gb/s bi-directional near line rate throughput
- Hardware acceleration and offloads for stateless TCP/IP, TCP Offload Engine (TOE)
- Improved small packet performance
- Integrated PHY and MAC
- Support for Preboot eXecution Environment (PXE)
- Support for SR-IOV (for Window

Dual-port 10 Gigabit Ethernet Throughput

The HP 530FLR adapter delivers 20,000 Mbps full duplex Ethernet transfer rate per port (40 Gbps aggregate full duplex), providing the network performance needed to improve response times and alleviate bottlenecks that impact performance of next generation data centers. 10Gb Ethernet bandwidth is ideal for high performance computing, database clusters, and more.

Jumbo Frames

The HP 530FLR adapter supports jumbo frames (also known as extended frames), permitting up to a 9K byte (KB) transmission unit (MTU) when running Ethernet I/O traffic. This is over 5X the size of a standard 1500-byte Ethernet frame. With jumbo frames, networks can achieve higher throughput performance and greater CPU utilization. These attributes are particularly useful for database transfer and tape backup operations.

TCP/IP Stateless Offloading

TCP, IP, UDP checksum offload, Large Send Offload (LSO), TCP, Segmentation Offload (TSO). These features optimize host efficiency, leaving the CPU available for other duties.

MSI and MSI-X

Message Signaled Interrupt (Extended) provides performance benefits for multi-core servers by load balancing interrupts between CPUs/cores.

802.1Q VLANs

IEEE 802.1Q virtual local area network (VLAN) protocol allows each physical port of the HP 530FLR adapter to be separated into multiple virtual NICs for added network segmentation and enhanced security and performance. VLANs increase security by isolating traffic between users. Limiting the broadcast traffic to within the same VLAN domain also improves performance.

TOE

TCP/IP Offload Engine (TOE) shifts the processing of data in the TCP protocol stack from the server CPU to the adapter's processor, freeing server CPU cycles for other operations.

Single-Root I/O Virtualization

Single-Root I/O Virtualization (SR-IOV) provides a mechanism to bypass the host system hypervisor in virtual environments providing near metal performance and server efficiency. SR-IOV provides mechanism to create multiple Virtual Functions (VFs) to share single PCIe resources. The device is capable of SR-IOV, and requires Server BIOS support, controller firmware, and OS supports

Optimized for Virtualization

I/O Virtualization support for VMware NetQueue and Microsoft VMQ help meet the performance demands of consolidated virtual workloads.

Standard Features

FlexibleLOM slot Compatibility

Compatible with HP FlexibleLOM slot for select HP Rack servers

Network Adapter Teaming The HP 530FLR adapter support for NIC teaming helps IT administrators increase network fault tolerance and increased network bandwidth, The team of adapters can work together as a single virtual adapter. The HP 530FLR provides support for several different types of teaming enabling IT administrators to optimize availability, improve performance and help reduce costs

Network Management

Management Support

The HP 530FLR adapter can be administered from HP Systems Insight Manager (SIM). The adapters can be managed individually or in teams, providing SNMP based statistics for reporting purposes. The HP 530FLR adapter can also be managed by other applications with SNMP support.

Server Integration

Server Integration The HP 530FLR adapter is a validated, tested, and qualified solution that is optimized for HP ProLiant servers. HP validates a wide variety of major operating systems drivers with the full suite of web-based enterprise management utilities including HP Intelligent Provisioning and HP Systems Insight Manager that simplify network management.

This approach provides a more robust and reliable networking solution than offerings from other venders and provides users with a single point of contact for both their servers and their network adapters.

Configuration Utilities

Each HP 530FLR ships with a suite of operating system-tailored configuration utilities that allow the user to enable initial diagnostics and configure adapter teaming. This includes a patented teaming GUI for Microsoft Windows operating systems. Additionally, support for scripted installations of teams in a Microsoft Windows environment allow for unattended OS installations.

LED Indicators

The colored LEDs on each port of the HP 530FLR adapter indicate link status and link activity.

Preboot eXecution **Environment (PXE)**

PXE allows the server to boot over the network and download software residing in the network.

HP Sea of Sensors 3D

Support for HP's Sea of Sensors which is a collection of 32 sensors that automatically track thermal activity - heat - across the server. When temperatures get too high, sensors can kick on fans and make other adjustments to reduce energy usage. What makes it better is the upgrade from all six fans kicking on at one time to a new system where only one kicks on - the one in proximity of the area that started heating up - thus reducing the amount of energy used for cooling.

Warranty

Maximum: The remaining warranty of the HP product in which it is installed (to a maximum three-year, limited warranty).

Minimum: One year limited warranty.

Additional information regarding worldwide limited warranty and technical support is available at: http://h18004.www1.hp.com/products/servers/platforms/warranty/index.html



Service and Support

Service and Support

HP Technology Services

HP Technology Services offers you consultants and support experts to solve your most complex infrastructure problems. We help keep your business running, boost availability, and avoid downtime.

Protect your business beyond warranty with HP Care Pack Services

When you buy HP Options, it's also a good time to think about what level of service you may need. HP Care Pack services provide total care and support expertise with committed response choices designed to meet your IT and business need.

HP Foundation Care services deliver scalable support-packages for HP industry-standard servers and software. You can choose the type and level of service that is most suitable for your business needs. New to this portfolio is HP Collaborative Support. If you are running business critical environments, HP offers Proactive Care or Critical Advantage. These services help you deliver high levels of application availability through proactive service management and advanced technical response.

Here is the support service recommendation from the Foundation Care and Proactive Care portfolio. For customized support service solution, HP can work with you to tailor a service solution for your unique support requirements using broader services portfolio of Foundation Care and Proactive Care.

Recommended HP Care Pack Services for optimal satisfaction with your HP product

Recommended Services

3-Year HP 24x7 4 hour Response, Hardware Support Onsite Service

Provides you with rapid remote support and if required an HP authorized representative who will arrive on site any time and day of the year to begin hardware maintenance service within 4 hours of the service request being logged.

http://h20195.www2.hp.com/V2/GetPDF.aspx/5982-6547EEE.pdf

OR

3-Year HP 24x7 4 hour Response, HP Collaborative Support

Offers customers a single point of contact for server problem diagnosis, hardware problem resolution, and basic software problem diagnosis, fault isolation, and resolution if available to HP. If the problem is with HP HW, the representative will arrive on site any time and day of the year to begin hardware maintenance service within 4 hours of the service request being logged. In case, the issue is with HP or supported third-party software product and cannot be resolved by applying known fixes, HP will contact the third-party vendor and create a problem incident on your behalf.

HP ProLiant Server Hardware Installation

Provides for the basic hardware installation of HP branded servers, storage devices and networking options to assist you in bringing your new hardware into operation in a timely and professional manner http://h20195.www2.hp.com/V2/GetPDF.aspx/5981-9356EN.pdf



Service and Support

Related HP Care Pack Services to enhance your HP product experience

Related Services

3-Year HP 24x7 4 hour Response, Proactive Care or Critical Advantage

Helps optimize your systems and delivers high levels of application availability through proactive service management and advanced technical response. A skilled Technical Manager will own your query or issue end to end until resolved, delivering a single point of contact for you http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA3-2140ENW.pdf

OR

3-Year HP 6-hour Onsite Call-to-Repair, HP Collaborative Support

Offers customers a single point of contact for server problem diagnosis, hardware problem resolution to return the hardware in operating condition within 6 hours of the initial service request to the HP Global Solution Center, and basic software problem diagnosis, fault isolation, and resolution if available to HP. In case, the issue is with HP or supported third-party software product and cannot be resolved by applying known fixes, HP will contact the third-party vendor and create a problem incident on your behalf.

HP Proactive Select Service

Provides a flexible way to purchase HP best-in-class consultancy and technical services. You can buy Proactive Select Service Credits when you purchase your hardware and then use the credits over the next 12 months. http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA2-3842ENN.pdf

Insight Remote Support

Provides 24 X 7 remote monitoring, proactive notifications, and problem resolution. Learn more http://www.hp.com/go/insightremotesupport

HP Support Center

Personalized online support portal with access to information, tools and experts to support HP business products. Submit support cases online, chat with HP experts, access support resources or collaborate with peers. Learn more http://www.hp.com/go/hpsc

HP's Support Center Mobile App* allows you to resolve issues yourself or quickly connect to an agent for live support. Now, you can get access to personalized IT support anywhere, anytime. HP Insight Remote Support and HP Support Center are available at no additional cost with a HP warranty, HP Care Pack or HP contractual support agreement.

*HP' Support Center Mobile App is subject to local availability

Parts and materials

HP will provide HP-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements. Supplies and consumable parts will not be provided as part of this service; standard warranty terms and conditions apply. Parts and components that have exceeded their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual or the technical product data sheet will not be provided, repaired or replaced as part of this service.



Service and Support

Warranty / Service Coverage

For ProLiant servers and storage systems, this service covers HP-branded hardware options qualified for the server, purchased at the same time or afterward, internal to the enclosure, as well as external monitors up to 22" and tower UPS products; these items will be covered at the same service level and for the same coverage period as the server unless the maximum supported lifetime and/or the maximum usage limitation has been exceeded. Coverage of the UPS battery is not included; standard warranty terms and conditions apply.

The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by HP due to malfunction. It does not apply to any exchange of Disk or SSD/Flash Drives that have not failed. SSD/Flash Drives that are specified by HP as consumable parts and/or that have exceeded maximum supported lifetime and/or the maximum usage limit as set forth in the manufacturer's operating manual or the technical data sheet are not eligible for the defective media retention service feature option.

For more information

To learn more on services for HP ESSN Options, please contact your HP sales representative or HP Authorized Channel Partner. Or visit: http://www.hp.com/services/proliant or www.hp.com/services/bladesystem



Related Options

| Direct Attach Cable | HP BladeSystem c-Class Small Form-Factor Pluggable .5m 10GbE Copper Cable | 487649-B21 |
|----------------------|---|------------|
| | HP BladeSystem c-Class Small Form-Factor Pluggable 1m 10GbE Copper Cable | 487652-B21 |
| | HP BladeSystem c-Class Small Form-Factor Pluggable 3m 10GbE Copper Cable | 487655-B21 |
| | HP BladeSystem c-Class Small Form-Factor Pluggable 5m 10GbE Copper Cable | 537963-B21 |
| | HP X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable | JD097C |
| | HP X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable | JD096C |
| | HP X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable | JD095C |
| | HP X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable | JG081C |
| | HP X240 10G SFP+ SFP+ 7m Direct Attach Copper Cable | JC784C |
| | NOTE: Direct Attach Cable (DAC) must be purchased separately for copper | 30.010 |
| | environments. | |
| Fiber Optic Modules | HP BladeSystem c-Class 10Gb Short Range Small Form-Factor Pluggable Option | 455883-B21 |
| • | HP BladeSystem c-Class 10Gb Long Range Small Form-Factor Pluggable Option | 455886-B21 |
| | NOTE: Fiber transceivers and cables must be purchased separately for fiber-optic | |
| | environments. | |
| Fiber Optic Cables | HP 2M LC-SC Cable Kit (2Gb to 1Gb) | 221691-B21 |
| • | 5M LC-SC Cable Kit (2Gb to 1Gb) | 221691-B22 |
| | HP 15M LC-SC Cable Kit (2Gb to 1Gb) | 221691-B23 |
| | HP 2m LC-LC FC Cable Kit | 221692-B21 |
| | 5m LC-LC FC Cable Kit | 221692-B22 |
| | HP 15m LC-LC FC Cable Kit | 221692-B23 |
| | HP 30m LC-LC FC Cable Kit | 221692-B26 |
| | HP 50m LC-LC FC Cable Kit | 221692-B27 |
| | | AJ833A |
| | HP LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable | |
| | HP LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable | AJ834A |
| | HP LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable | AJ836A |
| | HP LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable | AJ837A |
| | HP LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable | AJ838A |
| | HP LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable | AJ839A |
| | NOTE: Fiber transceivers and cables must be purchased separately for fiber-optic | |
| | environments. | |
| | NOTE: For additional information on 10Gb cable specifications go to: | |
| | http://www.hewlett-packard.com/rnd/pdfs/10gig_cabling_technical_brief.pdf | |
| Additional Supported | HP X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable | JD095C |
| Cables | HP X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable | JD096C |
| (Plug into HPN5900) | HP X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable | JD097C |
| | HP X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable | JG081C |
| | HP X240 10G SFP+ to SFP+ 7m Direct Attach Copper Cable | JC784C |
| | HP X240 QSFP+ 4x10G SFP+ 1m DAC Cable | JG329A |
| | HP X240 QSFP+ 4x10G SFP+ 3m DAC Cable | JG330A |
| | HP X240 QSFP+ 4x10G SFP+ 5m DAC Cable | JG331A |
| | | |



Related Options

| Additional Supported | HP X242 10G SFP+ to SFP+ 1m Direct Attach Copper Cable | J9281B |
|-------------------------------|--|------------|
| Cables | HP X242 10G SFP+ to SFP+ 3m Direct Attach Copper Cable | J9283B |
| (Plug into HPN6600) | HP X242 10G SFP+ to SFP+ 7m Direct Attach Copper Cable | J9285B |
| Gigabit Server Adapters | HP NC112T PCI Express Gigabit Server Adapter | 503746-B21 |
| | HP NC360T PCI-E Dual Port Gigabit Server Adapter | 412648-B21 |
| | HP NC364T PCI-E Quad Port Gigabit Server Adapter | 435508-B21 |
| | HP NC365T 4-port Ethernet Server Adapter | 593722-B21 |
| | HP NC373T PCI-E Multifunction Gigabit Server Adapter | 394791-B21 |
| | HP NC373F PCI-E Multifunction 1000SX Gigabit Svr Adapter | 394793-B21 |
| | HP NC375T PCI Express Quad Port Gigabit Server Adapter | 538696-B21 |
| | HP NC382T PCI Express Dual Port Multifunction Gigabit Server Adapter | 458492-B21 |
| | HP Ethernet 1Gb 4-port 331T Adapter | 647594-B21 |
| | HP Ethernet 1Gb 2-port 332T Adapter | 615732-B21 |
| | HP Ethernet 1Gb 2-port 361T Adapter | 652497-B21 |
| 10 Gigabit Server Adapters | NOTE: A minimum of two Gigabytes (2 GB) of server memory is required per each adapter. | |
| | HP NC522SFP Dual Port 10GbE Gigabit Server Adapter | 468332-B21 |
| | HP NC523SFP 10Gb 2-port Server Adapter | 593717-B21 |
| | HP NC524SFP Dual Port 10GbE Module | 489892-B21 |
| | NOTE: NC524SFP is available only on DL370 G6, ML370 G6, DL580 G7, DL585 G7, and DL980 G7. | |
| | HP NC550SFP Dual Port 10GbE Server Adapter | 581201-B21 |
| | HP NC552SFP 10Gb 2-port Ethernet Server Adapter | 614203-B21 |
| | HP Ethernet 10Gb 2-port 530SFP Adapter | 652503-B21 |
| | HP Ethernet 10Gb 2-port 530T Adapter | 656596-B21 |
| | HP Ethernet 10Gb 2-port 560SFP+ Adapter | 665249-B21 |
| | HP Ethernet 10Gb 2-port 561T Adapter | 716591-B21 |
| | HP Ethernet 10Gb 2-port 570SFP+ Adapter | 718904-B21 |



Related Options

FlexibleLOM Adapters

NOTE: A minimum of two Gigabytes (2 GB) of server memory is required per each adapter.

Ethernet Adapters

| HP Ethernet 1Gb 4-port 331FLR Adapter | 629135-B21 | | | |
|---|------------|--|--|--|
| HP Ethernet 1Gb 4-port 366FLR Adapter | 665240-B21 | | | |
| HP Ethernet 10Gb 2-port 560FLR-SFP+ Adapter | 665243-B21 | | | |
| HP Ethernet 10Gb 2-port 561FLR-T Adapter | 700699-B21 | | | |
| HP Ethernet 10Gb 2-port 570FLR-SFP+ Adapter | 717491-B21 | | | |
| FlexFabric Adapters | | | | |
| HP FlexFabric 10Gb 2-port 526FLR SFP+ Adapter | 629138-B21 | | | |
| HP FlexFabric 10Gb 2-port 533FLR-T Adapter | 700759-B21 | | | |

NOTE: Please see the QuickSpecs for Technical Specifications and additional

information: www.hp.com/go/ProLiantNICs

HP FlexFabric 10Gb 2-port 534FLR-SFP+ Adapter

HP FlexFabric 10Gb 2-port 554FLR-SFP+ Adapter



700751-B21

629142-B21

Technical Specifications

General Specifications Network Processor Broadcom BCM57810S chipset

Data Rate Two ports, each at 20 Gbps full duplex; 40 Gbps aggregate full duplex

theoretical bandwidth.

Onboard Memory 256MB

Bus Type PCI Express v2.0 (Gen 2) x8 (FlexibleLOM slot)

Form Factor FlexibleLOM

IEEE Compliance 802.3, 802.1ab, 802.3x, 802.3ad, 802.3p, 802.1q, 802.3ae, 802.1Qau, 802.3ap

Power and Environmental Operating

Specifications

Temperature 32° to 131° F (0° to 55° C)

10% to 90% non-condensing

Power <12W

Emissions USA: FCC Part 15 Class A; Canada: ICES=--3, Issue 4; Japan: VCCI V3 (2010.04)

Class A; International: EN55022:2006 + A1:2007 Class A; International: EN55024:1998+A1:2011+A2; EN61000-3-2:2006, EN61000-3-3:2008; Taiwan: BSMI, CNS13438 (2006) Class A; Australia/New Zealand (AS/NZS):

EN55022:2006+A12007 class A; Korea: KN22 Class A, KN24

Safety 6 of 6

Other UL Mark (USA and Canada)

CE Mark EN 60590

Humidity

Operating System Support Microsoft Windows Server 2008, Server 2008R2, and HPC Server 2008, 32 and 64-bit

Microsoft Windows Server Hyper-V Red Hat Enterprise Linux 5.x and 6.0

SLES 10 and 11 VMware 4.0 and 4.1

VMware ESX/ESXi 4.1 and ESXi 5.0

Solaris 10

NOTE: For more Linux OS support & certification information, please visit our the ProLiant & BladeSystem

Server Linux matrix: http://h18004.www1.hp.com/products/servers/linux/hplinuxcert.html



Technical Specifications

Environment-friendly Products and Approach

End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return, trade-in, and recycling programs in many geographic areas. For trade-in information, please go to: http://www.hp.com/go/green. To recycle your product, please go to: http://www.hp.com/go/green or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/green. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

© Copyright 2013 Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice.

Windows is a US registered trademark of Microsoft Corporation.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

