

# Data Sheet Fujitsu Display P27T-7 LED Displays

Superior display: 69 cm (27-inch) widescreen Cutting edge display technology and innovative Green solutions

Enjoy perfect picture quality with 3.7 Mio pixels, outstanding ergonomics and usability as well as comfortable energy saving solutions of this 69 cm (27-inch) widescreen Fujitsu P Line display.

In Plane Switching (IPS) panel technology with an ultra wide viewing angle of 178°, LED backlight technology and high precision color performance

Unique energy saving solutions with 0.0 Watt power consumption in off mode (via HDMI, DVI and VGA), ECO button - direct access to power saving operation mode

Auto Brightness Control (ABC) - Sensor dims the brightness optimized to the working environment - and also saves energy

Optimized and relaxed position - with ergonomic stand featuring height adjust, swivel, tilt and 90° rotation

Highly flexible connectivity through different interfaces -  $4\,x$  USB, DisplayPort, HDCP (via DVI-D), HDMI 1.4, DVI and Analog

Representative design with space saving front frame and smart details like connector cover and discretely integrated speakers and sensor keys

Due to the DisplayView Manageability tools ready for remote inventory gathering and for remote execution of configuration tasks

DICOM greyscale standard compatible preset for clinical review applications

























# Technical details

Special features	
Special reactives	In Plane Switching (IPS), LED backlight panel, DICOM Greyscale Standard Display Function compatible gamma preset,
	Color accuracy average DeltaE<2, 0-Watt power save mode (with HDMI, DVI, VGA), ECO button, Auto Brightness Control (ABC), DisplayView™ IT Suite, 24/7 usage
Ergonomic stand	Control (ABC), Displayview 11 Suite, 24/7 usage
Stand	4-in-1 Stand
Height adjust range	130 mm
Picture height over desk (min)	45 mm
Rotation to portrait	90° (AutoPivot)
Tilt angle	-5° / +35°
Swivel angle	340°
-	340
Picture performance Panel and backlit	
Screen Surface Treatment	IPS/LED
	3H hard coating, Anti-glare 1000:1
Contrast - typical	
Contrast - advanced	20,000,000:1
Response time gray to gray typical	5 ms (in Video mode)
Viewing angle (h/v) - typical	178°/178° CR10:1
Color performance	16.7 million colors (8-bit)
Brightness - typical	350 cd/m
Size and resolution	
Aspect ratio	16:9
Diagonal Size	68.5 cm (27-inch)
Resolution (native)	2560 x 1440 pixel (recommended)
Resolution (interpolated)	2560 x 1600 pixel via DisplayPort and Dual Link DVI, 1920 x 1200 pixel, 1680 x 1050 pixel, 1600 x 1200 pixel, 1400 x 900 pixel, 1280 x 800 pixel, 1280 x 768 pixel, 1024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
Resolution note	2560x1440 via DisplayPort, Dual Link DVI, HDMI 1.4 up to 1920x1200 via VGA and DVI
Video modes	1080i/p, 720i/p, 576i/p, 480i/p
Picture size	597 x 336 mm
Pixel Pitch	0.233 mm
Frequencies	
Horizontal	27 - 100 kHz
Vertical	50 - 75 Hz
Frequencies - bandwidth	360 MHz (DisplayPort)
Connectivity	
DisplayPort	1 x DisplayPort 1.2
HDMI	1 x HDMI 1.4
DVI	1 x DualLink DVI
VGA/D-SUB	1 x D-SUB
Audio signal input	3.5 mm stereo phone jack
Audio sound output	2 x 2.0 W
USB downstream	4 x USB 3.0
USB upstream	1 x USB
Ease-of-use menu	1 A 030
Languages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese traditional, Chinese simply
Brightness / Contrast	Brightness, Contrast, Black level, Auto Brightness, Auto level
Color	9300K, 7500K, 6500K, Native, Custom Color (R,G,B)
Image adjust	Clock, Phase, H-Position, V-Position, Expansion, Saturation, Sharpness
Audio	Mute, Volume
	ואוטנב, אטוטוווכ

la formation	Madel name C/N Desclution/made Cional input ACD Chabus ADC Chabus			
Information	Model name, S/N, Resolution/mode, Signal input, ACR Status, ABC Status			
Setup	Input select, Language, DDC-CI, OSD-Timeout, Factory recall			
Power consumption (typical)				
0 watt power save	0.0 W			
Hard switch off	0.0 W			
Operating with EPA settings	31 W			
Operating maximum brightness	49 W			
Power supply display	integrated			
Power notes	without sound, without USB; 0-Watt power save mode with HDMI, DVI, VGA; 0.4 W in power save mode with DisplayPort;			
Electrical values				
Rated voltage range	100 V - 240 V			
Rated frequency range	50 Hz - 60 Hz			
Protection class	1			
Compliance				
Europe	EN 60950, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration			
Model	P27T-7			
Germany	TÜV GS			
Russia	GOST			
USA/Canada	FCC Class B, cUL			
Australia/New Zealand	C-Tick (planned)			
Japan	VCCI			
South Korea	KC (planned)			
Argentina	TÜV-S			
China	CCC (planned)			
Saudi Arabia	SASO			
Global	TCO Displays 6.0, ENERGY STAR® 6.0 in progress, EPEAT® Gold (dedicated regions), ISO9241-307 (Pixel fault class I)			
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/			
Quality and Reliability	napsspr.s.nej restream sines, centine desi			
MTBF (demonstrated)	70000 h			
Dimensions / Weight / Environmental	7000011			
Dimension without stand (W x D x H)	644 x 72 x 383 mm			
Dimension with stand (W x D x H)	644 x 227 x 405 mm			
Weight (packed)	13 kg			
Weight (unpacked)	10 kg			
Weight (Monitor only)	7 kg			
Operating ambient temperature	5 - 35°C			
Miscellaneous	3 33 6			
Miscellaneous	VESA DDC/ CI, Standardized mounting interface VESA FP MP MI 100 mm, Kensington lock prepared			
Color	Marble grey			
Package content	matric grey			
Display delivered accessories	DisplayPort data cable 1.8 m, DVI-D Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power			
Display delivered decessories	cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet			
Display delivered accessories notes	Data cables, USB cable and audio cable detachable on display			
Order information				
Order Code	S26361-K1442-V140			
EAN-No.	4051554454319			
Warranty				
Standard Warranty	3 years			
Service level	Collect & Return Service (depending on country specific requirements)			
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty			
Spare Parts availability	5 years after end of product life			
Service Weblink	http://www.fujitsu.com/fts/services/support			

Data Sheet Fujitsu Display P27T-7 LED Displays					

## More information

#### **Fujitsu OPTIMIZATION Services**

In addition to Fujitsu Display P27T-7 LED, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### **Computing Products**

www.fujitsu.com/global/services/computing/

#### Software

www.fujitsu.com/software/

#### More information

Learn more about Fujitsu Display P27T-7 LED, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

http://www.fujitsu.com/fts/displays

#### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment/



### Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/

Copyright © Fujitsu Technology Solutions

#### Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

#### Contact

FUJITSU Technology Solutions Website: www.fujitsu.com/fts 2013-01-09 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

Copyright © Fujitsu Technology Solutions