QuickSpecs

Overview

Models

NVIDIA Quadro K4100M 4GB Graphics

E5Z77AA

Introduction

The NVIDIA Quadro® K4100M graphics board is a graphics processing unit (GPU) module designed using the MXM™ version 3.1 Type B specification. This graphics module provides high level graphics capabilities for the most demanding professional product design/development applications and workflows. This module is also ideal for demanding digital media, including video, workflows.

Performance and Features

The NVIDIA Quadro K4100M offers:

- Large fast 4 GB GDDR5 memory
- Lastest NVIDIA Kepler GPU architecture
- 1152 CUDA cores
- Extensive ISV application certifications

Compatibility

Supported on HP Z1 G2 workstation.

Service and Support

The NVIDIA Quadro K4100M has a one-year limited warranty or the remainder of the warranty of the HP product in which it is installed. Technical support is available seven days a week, 24 hours a day by phone, as well as online support forums. Parts and labor are available on-site within the next business day. Telephone support is available for parts diagnosis and installation. Certain restrictions and exclusions apply.



QuickSpecs

Technical Specifications

Form Factor MXM v3.1 Type B (82mm x 105mm)

Graphics Controller N15E-Q3, 705MHz core clock

1152 CUDA cores

Bus Type PCI Express Gen 3 x16 (part of MXM v3.1 connector)

4GB GDDR5 Memory

256 bit wide interface

3200MHz. 102.4 GB/s

Connectors One MXM v3.1 connector (285-pin)

Maximum Resolution Maximum number of active displays: 4

In Z1 G2 application:

- Internal Display: 2560x1440

- External Display via DP connector: 2560x1600

- External Display via optional Thunderbolt module: Two 3840x2160

RAMDAC Not Applicable

Image Quality Features Each color component can be processed at up to 32-bit floating point precision and displayed at up to 12-

bit precision.

Advanced FXAA and TXAA antialiasing. 16K Texture and Render Processing.

MPEG-2 HD and WMV HD video playback (1920x1080p).

H.264 hardware decode acceleration. Nvidia Scalable Geometry Engine.

AES-128 CTR/CBC/ECB decryption modes supported.

Nvidia 3D Vision Pro

Shading Architecture Shader Model 5.0 support **Supported Graphics APIs** Full IEEE 764-2008 32-bit

DirectX 11.1 Shader Model 5.0

OpenGL 4.3

Compute API support for NVIDIA CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python and Fortran

Available Graphics

Windows 7 64-bit Windows 8.1 64-bit **Drivers**

> SUSE Linux Enterprise Desktop 11 64-bit Red Hat Enterprise Linux 6 Workstation 64-bit

See www.hp.com/go/support for HP supported NVIDIA graphics drivers

© Copyright 2014 Hewlett-Packard Development Company, L.P.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. The information contained herein is subject to change without notice.

