Overview

Models

NVIDA Quadro 1000M 2GB Graphics

A2G98AV

Introduction

The NVIDIA Quadro® 1000M graphics board (N12P-Q1 / P1076) is an MXM[™] version 3.0 Type A (82 mm by 70 mm) form factor graphics add-in card based on the Quadro® graphics processing unit (GPU). This graphics board is targeted for entry to midrange professional 3D workstation graphics applications.

Performance and Features

Supported on HP Z1 workstation.

Service and Support

The NVIDIA Quadro 1000M has a one-year limited warranty or the remainder of the warranty of the HP product in which it is installed. Technical support is available seven days a week, 24 hours a day by phone, as well as online support forums. Parts and labor are available on-site within the next business day. Telephone support is available for parts diagnosis and installation. Certain restrictions and exclusions apply.



QuickSpecs

Technical Specifications

Form Factor	MXM v3.0 Type A (82mm x 70mm)
Graphics Controller	N12P-Q1, 700MHz core clock
Bus Type	PCI Express x16 (part of MXM v3.0 connector)
Memory	2GB DDR3, 128-bit wide interface, 900MHz
Connectors	One MXM v3.0 connector (285-pin)
Maximum Resolution	2 x 2560x1600 @ 60Hz digital displays In Z1 application: - Internal Display: 2560x1440 - External Display via DP connector: 2560x1600
RAMDAC	Not Applicable
Image Quality Features	Capable of 10-bit per channel (3 channels) internal display processing, including hardware support for 10-bit per channel scan-out 64-bit texture filtering and blending Advanced vertex and pixel shaders, antialiasing, 16x anisotropic filtering MPEG-2 HD and WMV HD video playback (1920x1080p) H.264 hardware decode acceleration AES-128 CTR/CBC/ECB decryption modes supported Advanced video algorithms NVIDIA Digital Vibrance Control 3.0
Shading Architecture	Shader Model 5.0 support 96 processor cores
Supported Graphics APIs	Full IEEE 764-2008 32-bit or 64-bit precision DirectX 11.0 Shader Model 5.0 OpenGL 4.0 Compute API support for NVIDIA CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python and Fortran
Available Graphics Drivers	Windows 7 32-bit and 64-bit SUSE Linux Enterprise Desktop 11 HP Linux Installer Kit
Power Consumption	See www.hp.com/go/support for HP supported NVIDIA graphics drivers 42W

© Copyright 2012 Hewlett-Packard Development Company, L.P.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. The information contained herein is subject to change without notice.

