




Features

- Native XGA (1024 x 768) Resolution
- 3,000 ANSI Lumens, 10,000:1 High Contrast Ratio
- SmartEco™ Power Saving Technology
- Full 3D Ready
- Up to 7,000 Hours Lamp Life
- PointWrite Interactive Kit Compatible



Input and Output Terminals



- ① Computer in 1 & 2 (D-sub 15pin)
- ② Monitor Out (D-sub 15pin)
- ③ S-Video In (Mini DIN 4pin)
- ④ Composite Video in (RCA)
- ⑤ HDMI
- ⑥ LAN
- ⑦ USB (Type Mini B)
- ⑧ PointWrite
- ⑨ RS232 (DB-9pin)
- ⑩ Audio In/Out (Mini Jack)
- ⑪ Audio (L/R)

Specifications

Projection System	DLP®																												
Native Resolution	XGA (1024x768)																												
Brightness	3,000AL																												
Contrast Ratio	10,000:1																												
Display Color	1.07 Billion Colors																												
Lens	F2.5, f=5.1mm																												
Aspect Ratio	Native 4:3 (5 aspect ratio selectable)																												
Throw Ratio	0.43																												
Image Size (Diagonal)	68"~85", Optimal 78"																												
Zoom Ratio	Fix																												
Lamp Type	230W																												
Lamp (Normal/Economic Mode)*	4000/5000/7000 hours																												
Keystone Adjustment	1D, Vertical +/- 40 degrees																												
Projection Offset	123% ±5%																												
Resolution Support	VGA(640 x 480) to UXGA(1600 x 1200)																												
Horizontal Frequency	15~102KHz																												
Vertical Scan Rate	23~120Hz																												
Compatibility	HDTV Compatibility: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p Video Compatibility: NTSC, PAL, SECAM,																												
Interface	<table border="0"> <tr> <td>Computer in (D-sub 15pin)</td> <td>x 2(Shared with component)</td> </tr> <tr> <td>Monitor out (D-sub 15pin)</td> <td>x 1</td> </tr> <tr> <td>Composite Video in (RCA)</td> <td>x 1</td> </tr> <tr> <td>S-Video in (Mini DIN 4pin)</td> <td>x 1</td> </tr> <tr> <td>HDMI</td> <td>x 1</td> </tr> <tr> <td>Audio in (Mini Jack)</td> <td>x 1</td> </tr> <tr> <td>Audio out (Mini Jack)</td> <td>x 1</td> </tr> <tr> <td>Audio L/R</td> <td>x 1</td> </tr> <tr> <td>Speaker</td> <td>10W x 2</td> </tr> <tr> <td>USB (Type mini B)</td> <td>x 2 (PointWrite interactive module)</td> </tr> <tr> <td>USB (Type B)</td> <td>x 1 (FW download)</td> </tr> <tr> <td>RJ45</td> <td>x 1 (LAN control)</td> </tr> <tr> <td>RS232 (DB-9pin)</td> <td>x 1</td> </tr> <tr> <td>IR Receiver</td> <td>x 2 (Front)</td> </tr> </table>	Computer in (D-sub 15pin)	x 2(Shared with component)	Monitor out (D-sub 15pin)	x 1	Composite Video in (RCA)	x 1	S-Video in (Mini DIN 4pin)	x 1	HDMI	x 1	Audio in (Mini Jack)	x 1	Audio out (Mini Jack)	x 1	Audio L/R	x 1	Speaker	10W x 2	USB (Type mini B)	x 2 (PointWrite interactive module)	USB (Type B)	x 1 (FW download)	RJ45	x 1 (LAN control)	RS232 (DB-9pin)	x 1	IR Receiver	x 2 (Front)
Computer in (D-sub 15pin)	x 2(Shared with component)																												
Monitor out (D-sub 15pin)	x 1																												
Composite Video in (RCA)	x 1																												
S-Video in (Mini DIN 4pin)	x 1																												
HDMI	x 1																												
Audio in (Mini Jack)	x 1																												
Audio out (Mini Jack)	x 1																												
Audio L/R	x 1																												
Speaker	10W x 2																												
USB (Type mini B)	x 2 (PointWrite interactive module)																												
USB (Type B)	x 1 (FW download)																												
RJ45	x 1 (LAN control)																												
RS232 (DB-9pin)	x 1																												
IR Receiver	x 2 (Front)																												
Dimensions (WxHxD)	11.3" x 14.6" x 7.31" (w/o Mirror) 11.3" x 14.6" x 7.9" (w Mirror)																												
Weight	11.02 lbs (5KG) w/o wall mount																												
Power Supply	AC100 to 240 V, 50 to 60 Hz																												
Power Consumption	typical 290W, stanby power <0.5W																												
Audible Noise	33/29 dBA (Normal/Economic mode)																												
Languages	Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages)																												
Picture Mode	Dynamic/Presentation/sRGB/Cinema/(3D)/User 1/User 2																												
Accessories (Standard)	Remote Control w/ Battery, Power Cord, User Manual CD Quick Start Guide, Warranty Card, VGA(D-sub 15pin) Cable Dust filter(C SKU), Wall mount kit (installation guide)																												
Accessories (Optional)	<table border="0"> <tr> <td>Spare Lamp Kit</td> <td>P/N: 5J.J8M05.011</td> </tr> <tr> <td>3D Glasses (DGD24)</td> <td>P/N: 5J.J7L25.001</td> </tr> <tr> <td>PointWrite kit (PW01U)</td> <td>P/N: 5J.J9A26.10E</td> </tr> </table>	Spare Lamp Kit	P/N: 5J.J8M05.011	3D Glasses (DGD24)	P/N: 5J.J7L25.001	PointWrite kit (PW01U)	P/N: 5J.J9A26.10E																						
Spare Lamp Kit	P/N: 5J.J8M05.011																												
3D Glasses (DGD24)	P/N: 5J.J7L25.001																												
PointWrite kit (PW01U)	P/N: 5J.J9A26.10E																												
UPC / Part #	8400460-3027-8 / 9H.J8M77.23A																												
Limited Warranty	3 Years Parts/Labor or 2,000 hours of lamp life.																												

*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.



MX852UST 02-10-14-BQus



BenQ America Corp.
www.BenQ.us

BenQ is a registered trademark of BenQ Corp. DLP® is a registered trademark of Texas Instruments. All rights reserved. Product names, logos, brands, and other trademarks featured or referred to in this materials are the property of their respective trademark holders. Specifications subject to change without notice.



Because it matters

