
# **QuickSpecs**

Overview



#### Models

HP ap5000 Magnetic Stripe Reader

BZ721AA

#### Introduction

Specifically designed for integration with HP ap5000 All-in-One Point-of-Sale (POS) system, this compact Magnetic Stripe Reader device provides high performance, reliable operations in a space saving design, with a clean look.

The Magnetic Stripe Reader (MSR) for HP ap5000 reads up to three tracks of information with a single swipe of a magnetic stripe card bi-directionally. An audible indicator (beeper) confirms a successful read. It automatically distinguishes between formats. At just 3.5 inches long - about the length of a credit card, with simple design and integration to HP ap5000, the MSR provides a clean look without any cable clutters.



### **QuickSpecs**

Overview

### **Key Benefits**

- Ideal for retail environments where counter space is limited
- Integrated MSR minimizes cable clutter
- Automatically distinguishes between magnetic data formats
- Reads up to three tracks of information with a single swipe
- Quick and easy card scanning with bi-directional read capabilities
- Flexible and accurate read with various swipe speed

#### Compatibility

Compatible with HP ap5000 AiO Point-Of-Sale system

NOTE: Not all models are available in all regions.

### Service and Support

Your HP branded Peripheral Limited Warranty is a three (3) year (HP Option Limited Warranty Period) parts replacement warranty.



## **QuickSpecs**

#### Technical Specifications

General Magnetic stripe formats ISO 7810, 7811 1/5, 7812, 7813

Card Swiping Direction Bi-directional

Card Swiping Speed 3 inch/sec to 100 inch/sec (7cm/sec to 250 cm/sec)

**Indicators** Buzzer

Decoding Method (ISO) Track 1: IATA

Track 2: ABA
Track 3: THRIFT

Mechanical Dimensions (LxWxH) 3.54 x 0.88 x 0.95 in (9.00 x 2.243 x 2.42 cm)

Interface/Connection Interface RS-232C (Default on COM4 as shipped from HP factory)

Connection Integrated internal Baud Rate 19200 bps (ASCII)

Data Bit 8
Parity None
Stop Bit 1
Flow Control None

Power Voltage (typical) 5 VDC +/- 10%

Environment Operating -10 to +60 degrees C.

Humidity 10% to 90% relative

**Drivers** Windows native, OPOS, JPOS

Operating Systems (compatible with)

Genuine Windows 7 Professional\* (32-bit)
Genuine Windows Vista® Business\*\* (32-bit)

Genuine Windows XP Professional

Genuine Windows Embedded POSReady 2009

\*This system may require upgraded and/or separately purchased hardware and/or a DVD drive to install the Windows 7 software and take full advantage of Windows 7 functionality. See

http://www.microsoft.com/windows/windows-7/ for details.

\*\* Certain Windows Vista product features require advanced or additional hardware. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit: http://www.windowsvista.com/upgradeadvisor. For Windows Vista system requirements, visit: http://www.windowsvista.com/systemrequirements

**Reliability** 1,000,000 card swipes minimum

Option kit contents Magnetic Stripe Reader for HP ap5000 AiO POS System

Copyright © 2011 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. The warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

